




1 THE INFORMATION CONTAINED HEREON IS PROPRIETARY AND CONFIDENTIAL TO DYNACOM CORPORATION. AND SHALL NOT BE USED OR DISCLOSED, IN WHOLE OR IN PART WITHOUT FIRST OBTAINING THE WRITTEN PERMISSION OF DYNACOM CORPORATION. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

ZONE	REV.	DESCRIPTION	DATE	APPV.
-	A	INITIAL RELEASE	04/18/2019	E.A.

Environmental Conditions
 TEMPERATURE RANGE
 STORAGE -40 to +70°C
 OPERATIONAL -10 to +60°C
 RELATIVE HUMIDITY (OPERATIONAL)
 MAXIMUM NONCONDENSING 93%

PHYSICAL:
 PANEL: SAE 1010, BLACK COATED.
 MANAGEMENT
 :HIGH-IMPACT,FLAME-RETARDANT
 PLASTIC,UL94V-0 RATED.



e-mail....sales@dynacomcorp.com
 www.dynacomcorp.com

DIMENSIONS: INCHES

NEXT ASSY: -	DRAWN: E.A. 04/18/2019	CHECKED: EA
TITLE PATCH PANEL BLANK 24 PORT 1 RU		DWG. NO. 2013-24HD
		SHEET 1 OF 1
		REV. A