

THE INFORMATION CONTAINED HEREON IS PROPRIETARY TO DYNACOM CORPORATION. AND SHALL NOT BE USED OR DISCLOSED, IN WHOLE OR IN PART WITHOUT FIRST OBTAINING THE WRITTEN PERMISSION OF DYNACOM CORPORATION. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

ZONE	REV.	DESCRIPTION	DATE	APPV.
-	A	INITIAL RELEASE	08/31/2020	C.Z.
-	B	ADD NEW GREEN ADAPTER	04/05/2023	C.Z.







Plate Material Cold Rolled Steel  
 Adapter Housing: PC  
 Color: Blue/ Green  
 Sleeve: Ceramic (Zirconia)  
 Adapter Plate Color FINISH-Black Powder Coat  
 Plate Dimensions (LxWxH) 130x30x1.5(mm)  
 Adapter Performance:  
 Durability >1000 times  
 Wavelength 850 & 1330nm  
 Insertion Loss ≤0.2dB  
 Temperature Stability Additional Loss≤0.2dB  
 Operating temperature -40 to +75°C  
 Storage temperature -40 to +75°C

P/N	Housing Color	Connector Polish
920A-SC-12	BLUE	UPC
920A-SCA12-GN	GREEN	APC



e-mail...sales@dynacomcorp.com  
 www.dynacomcorp.com

DIMENSIONS: mm

NEXT ASSY: -

DRAWN: C.Z. 08/31/20

CHECKED: EA

TITLE

FIBER OPTIC PANEL SC 12F SM

DWG. NO.

920A-SC-12

SHEET 1 OF 2

REV.

B